



<b>DISPLAY PANEL</b>	<b>Screen size</b>	32" (81 cm) diagonal
	<b>Aspect ratio</b>	16:9
	<b>Resolution</b>	1366 (H) x 768 (V) pixels
	<b>Pixel pitch</b>	0,51 (H) x 0,51 (V) mm
	<b>Useful screen</b>	698 (H) x 392 (V) mm
	<b>Brightness</b>	550 cd/m <sup>2</sup>
	<b>Contrast ratio</b>	1000:1 (typical) 5000:1 (dynamic)
	<b>View angle</b>	H: 180°, V: 180°
	<b>Colors</b>	16.77 Millions
	<b>Response time</b>	8 mSec
	<b>Front filter</b>	Safety glass; light transmission >90% Antireflective glass 2 + 2 mm + 0,38 mm plastic film (optional)
<b>INPUT</b>	<b>Video</b>	1 x BNC (CVBS, input only) 1 x mini DIN 4 pin (Y/C input only)
	<b>PC</b>	1 x Dsub-15 HD (Analog RGB, input only ) 1 x DVI-D (Digital RGB, input only)
	<b>Control</b>	1 x Dsub-9 female (input)
<b>FEATURES</b>	<b>Video compatibility</b>	PAL (BGH/D/I, 60), NTSC (M, 4, 43), SECAM
	<b>Video signal level</b>	CVBS: 1 Vpp/75 Ohm – nominal (with AGC) Y/C: 1 Vpp/75 Ohm – nominal (with AGC)
	<b>PC compatibility</b>	VGA – SXGA, Native (1366 x 768) Automatic frequency detection
	<b>PC signal level</b>	RGB: 0,7 Vpp/75 Ohm (RGB), TTL (HV) 1 x DVI-D (Digital RGB, input only)
	<b>Frequency range</b>	Horizontal: 15 KHz – 85KHz Vertical: 50 Hz – 85 Hz
	<b>Control interfaces</b>	Local keyboard (OSD) Infrared Remote Control (OSD) RS-232 Serial Port
<b>CONTROLS</b>	<b>Video</b>	Brightness, Contrast, Color, Sharpness, Hue Colour temperature Source selection
	<b>Geometry</b>	Self adjustment of picture dimension Free adjustment of picture position
	<b>Others</b>	Stand-by mode Status indication Programmable OSD position and aspect Multilanguage menu (D, E, F, GB, I) Display address selection DPMS Auto input search More on request
<b>PHYSICAL</b>	<b>Dimensions</b>	804 (W) x 500 (H) x 115 (D)
	<b>Weight</b>	31 Kg (without PC rack)
	<b>Mains voltage</b>	115/230 VAC +/- 15%, 50/60Hz
	<b>Power consumption</b>	200 W
	<b>Operating conditions</b>	Storage: -20°C to 65°C (max 85% RH not condensing) Working: 0°C to 50°C (max 85% RH not condensing)
	<b>Class protection</b>	IP30
	<b>Integrated PC rack</b>	Support micro ATX, Power switch, Reset switch Power supply socket